


PRODUCT FEATURES

- Individually shaped crescent ice.
- Protected by HoshiGuard Antimicrobial Agent.
- CycleSaver® technology includes a double-sided evaporator, uniquely crafted in stainless steel, which produces ice on both sides, resulting in more ice in less amount of time.
- EverCheck[™] Control Board with audible alarm and diagnostic features, designed to assist service technicians in diagnosing problems.
- Accessible digital operation panel allows for easy identification of operation status and cause of faults.
- Fully automated chemical cleaning function makes cleaning simple and saves time.
- Durable stainless steel exterior.
- Easily removable & cleanable air filters on front panel.
- Accessories : Manual, Scoop, check valve and 150mm adjustable legs included (water filter and optional hex bolt legs sold separately)

TECHNICAL DRAWING





For free 6 month extended warranty, register online within 4 weeks of purchase date. hoshizaki.com.au

ELECT, CONNECTION

Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes. Copyright © 2022 Hoshizaki Lancer Pty Ltd. All right reserved.

KM-40C-HC Crescent Ice Maker -Self-Contained





PRODUCT SPECIFICATION

Production Capacity / 24hrs

Bin Storage Capacity Freeze Cycle Time Ice Production / cycle Dimensions

Weight Net/Gross (kg)

AC Supply Voltage

Refrigerant Charge

Ambient Temp.

Operating Conditions:

Water Supply Temp. Water Supply Pressure

Cooling

Amperage

Approx. 41kg @ 21°C Air temp; 15°C Water Approx. 33kg @32°C Air temp; 21°C Water Approx. 16kg (Bin Control Setting Approx. 14kg) Approx. 23 Min (At. 21°C Air ; 15°C Water) Approx. 0.71kg/80pcs 452mm (W) x 610mm (D) x 838mm (H) (982-1005mm [H] with 150mm adjustable legs) (842mm [H] with optional hex bolt leg) Air 39/49 1 PHASE 220-240V 50Hz / 10amp Plug Running: 1.4A R290/68g 7-38°C 7-32°C 0.07-0.8MPa (0.7-8bar)

Voltage Range±6%Electrical consumption13.8kWh per 100kg ice (AT. 32°C; WT 21°C)Water Consumption / 24hrsApprox. 0.08m3/d (AT. 32°C; WT 21°C)Compatible Water FilterHLF10 Filter System (sold separately)

INSTALLATION REQUIREMENTS

- Qualified plumber required for installation.
- Allow 15cm clearance at rear, sides and top for proper air circulation and ease of maintenance.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

*Refer to manual for full installation & maintenance requirements.

