

KM-80C-HC Crescent Ice Maker -

Self-Contained




Model Number: 91000149

PRODUCT FEATURES

- Individually shaped crescent ice.
- Protected by HoshiGuard Antimicrobial Agent.
- CycleSaver® technology includes a double-sided evaporator, uniquely crafted in stainless steel, which produces ice on both sides, resulting in more ice in less amount of time
- EverCheck[™] Control Board with audible alarm and diagnostic features, designed to assist service technicians in diagnosing problems.
- Accessible digital operation panel allows for easy identification of operation status and cause of faults.
- Fully automated chemical cleaning function makes cleaning simple and saves time.
- Durable stainless steel exterior.
- Easily removable & cleanable air filters on front panel.
- Accessories: Manual, Scoop, legs, check valve. (water filter sold separately)

TECHNICAL DRAWING





For free 6 month extended warranty, register online within 4 weeks of purchase date.

hoshizaki.com.au

PRODUCT SPECIFICATION

Production Capacity / 24hrs	Approx. 68kg @ 21°C Air temp; 15°C Water
	Approx. 55kg @32°C Air temp; 21°C Water
Bin Storage Capacity	Approx. 34kg (Bin Control Setting Approx. 29kg)
Freeze Cycle Time	Approx. 23 Min (At. 21°C Air ; 15°C Water)
Ice Production / cycle	Approx. 1.15kg/130pcs
Dimensions	605mm (W) x 712mm (D) x 838mm (H)
	(982-1005mm [H] if installed with legs)
Cooling	Air
Weight Net/Gross (kg)	50/63
AC Supply Voltage	1 PHASE 220-240V 50Hz / 10amp Plug
Amperage	Running: 2.1A
Refrigerant Charge	R290/147g
Operating Conditions:	
Ambient Temp.	7-38°C
Water Supply Temp.	7-32°C
Water Supply Pressure	0.07-0.078MPa (0.7-7.8bar)
Voltage Range	198-254V
Electrical consumption	12.4kWh per 100kg ice (AT. 32°C; WT 21°C)
Water Consumption / 24hrs	Approx. 0.18m3/d (AT. 21°C; WT 15°C)
Compatible Water Filter	HLF10 Filter System (sold separately)

INSTALLATION REQUIREMENTS

- Qualified plumber required for installation.
- Allow 15cm clearance at rear, sides and top for proper air circulation and ease of mainatenance.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

*Refer to manual for full installation & maintenance requirements.







